

# TIG 220/250-1



- HF Mode-High Frequency
- 2T/4T Modes
- Selectable Down Slope time
- Selectable Post Flow time
- MMA Mode for various types of electrodes
- Compact and portable with light weight
- Digital Ammeters for easy viewing
- High duty cycle for industrial applications
- Generator friendly allows to work with diesel generators and to avoid failures due to its voltage spikes
- Protections including over-heat ,over-voltage,low-voltage and over-current



Decorations Industrial

### Processes

- TIG(GTAW)
- STICK(SMAW)

### Optional Accessories

- Earth cable and clamp
- Welding cable and holder
- Argon flow meter #00.5994
- WP-26-4m #32.0027.01
- Carry case #00.0200.02

Choice Prove TIG Series

## TIG 220

Model	Effective Input Amps	KW	Welding Current Range (A)	No-load Volts	Down Slope time	Rated Output at 40°C	Dimension	Net weight	Protection Class
TIG 220 220V±10% Single phase 50/60Hz	TIG:19 Stick: 27	TIG:5.0 Stick:7.2	TIG:10-220 Stick: 10-220	63	0-10S	200A@35%	L:410mm(16.1in.) W:146mm(5.7in.) H:278mm(10.9in.)	5.7Kg(12.5lb.)	IP23

## TIG 250-1

Model	Effective Input Amps	KW	Welding Current Range (A)	No-load Volts	Down Slope time	Rated Output at 40°C	Dimension	Net weight	Protection Class
TIG 250-1 220V±10% Single phase 50/60Hz	TIG:25 Stick: 35	TIG:6.1 Stick:8.8	TIG:10-220 Stick: 10-220	70	N/A	250A@40%	L:447mm(17.5in.) W:189mm(7.4in.) H:350mm(13.7in.)	10Kg(22lb.)	IP23

CE RoHS