

TROLLEYMIG300 DP



Decoration/ Light Industrial



Processes

- Pulsed MIG(GMAW-P)
- MIG(GMAW)
- FLUX CORED (FCAW)
- LIFT TIG
- MMA (SMAW)

Optional Accessories

- MIG 36/501D-Torch
- DIGIMIG-Torch
- TIG 17-Torch
- Earth Clamp
- Electrode Holder
- Foot Remote Control
- Spool Gun Torch
- Push Pull Torch
- Dual Gauge Regulator And Gas Hose
- Water Cooler
- Four Wheels Trolley

Model

Trolleymig300 DP

Input voltage	90-275V 50/60Hz		
Process	MIG	TIG	MMA
Effective current(A)	15.9	12.6	17.1
Rated input current(A)	20.6	16.3	22.1
Rated input power(KW)	14.3	11.3	15.4
Welding current(A)	20-300	10-300	10-300
Welding voltage(V)	15-29	10.4-22	20.4-32
Welding speed(m/min)	1.5-24		
No load voltage(V)	68	73	73
Duty cycle 40°C 10min	60% 300A / 100% 235A		
Efficiency	90%		
Power factor	0.7		
Insulation class	F		
Protection class	IP21S		
Dimensions(mm)	980*480*900		
Net weight(kg)	51		