

POWERMIG 200 LCD



Multi Functions PFC
Global voltage

3.8" LCD display

MIG manual
MIG Synergic

Earth clamp

Argon regulator
Gas hose

Electrode holder

Trolley

Lift Tig

Foot control

Spool gun

Decoration/ Light Industrial

1 Phase	DC	CC CV	VRD Safe
LCD Display	GLOBAL VOLTAGE WORLDWIDE USE	PROTE 275	MCU
3 ROOF	Spool Gun		

Processes

- MIG (GMAW)
- LIFT TIG
- FLUX CORED (FCAW)
- MMA (SMAW)

Optional Accessories

- MIG 15-Torch
- TIG 17-Torch
- Earth Clamp
- Electrode Holder
- Foot Remote Control
- Spool Gun Torch
- Dual Gauge Regulator And Gas Hose
- Two Wheels Trolley

Model	POWERMIG200 LCD					
Input voltage	90-275V 50/60Hz					
	1-110V			1-220V		
Process	MIG	TIG	MMA	MIG	TIG	MMA
Effective current(A)	23.4	17.7	17.7	17.7	13.9	20.2
Rated input current(A)	37	28	28	28	22	32
Rated input power(KW)	3.9	3.1	3.1	6.1	4.7	6.8
Welding current(A)	25-140	10-140	10-100	25-200	10-200	10-200
Welding voltage(V)	15.3-21	10.4-15.6	20.4-24	15.3-24	10.4-18	20.4-18
Welding speed(m/min)	1.5-4.5			1.5-16.5		
No load voltage(V)	65			65		
Duty cycle 40°C 10min	40% 140A/60% 115A/100%/90A			40% 200A/60% 165A/100% 130A		
Efficiency	80%			85%		
Power factor	0.99					
Insulation class	F					
Protection class	IP21S					
Dimensions(mm)	510*210*380					
Net weight(kg)	15.5					